

B1 Sub C2

5. (Twice Amended) A semiconductor testing method for testing semiconductor devices, comprising:

reading measurement data of an IDDQ measuring circuit configured to test semiconductor devices by applying an effective test vector, including a test vector data and data of good samples and faulty samples returned to a manufacturer;

supplying the test vectors to the good samples and the faulty samples;

determining a range of pass/fail decision criteria and effective address pairs for testing semiconductor devices; and

applying test vectors of the effective address pairs to the semiconductor devices for testing.

B2

9. (Twice Amended) A program with which a semiconductor testing method for testing semiconductor devices is executed by a computer in a semiconductor testing apparatus which comprises a read circuit, a determination circuit, and an IDDQ measuring circuit configured to test semiconductor devices by applying an effective test vector, the program comprising:

instructions configured to read measurement data including a test vector data and data of good samples and faulty samples returned to a manufacturer;

instructions configured to supply the test vector data to good samples and faulty samples;

instructions configured to determine a range of pass/fail decision criteria and effective address pairs for testing semiconductor devices; and

B2  
Cont'd

instructions configured to apply test vectors of the effective address pairs for testing.

B3 Sub  
Cont'd

13. (Twice Amended) A semiconductor testing method of specifying a faulty part in a semiconductor device, comprising:

reading measurement data of an IDDQ measuring circuit configured to test semiconductor devices by applying an effective test vector, wherein the measurement data includes a test program, test vector data, data of good samples and faulty samples returned to a manufacturer;

supplying test vector data to good and faulty samples;

determining a range of pass/fail decision criteria and effective address pairs for testing semiconductor devices in a manufacturing process;

applying test vectors of the effective address pairs to a semiconductor device;

and

specifying a faulty part within the semiconductor device by measuring an emission from the semiconductor device.

B4 Sub  
Cont'd

16. (Twice Amended) A semiconductor testing apparatus for specifying a faulty part in a semiconductor device, comprising:

a read circuit configured to read measurement data of an IDDQ measuring circuit configured to test semiconductor devices by applying an effective test vector, wherein

BA  
Coul  
See  
CP

the measurement data includes a test program, test vector data, data of good samples and faulty samples returned to a manufacturer;

a determination circuit configured to supply the test vector data to the good samples and faulty samples, and to determine a range of pass/fail decision criteria and effective address pairs for testing semiconductor devices in a manufacturing process; and

a faulty part specifying circuit configured to apply test vectors of the effective address pairs to a semiconductor device and to specify a faulty part by measuring an emission from the semiconductor device.

B5  
Coul  
See  
CP

19. (Twice Amended) A program with which a semiconductor testing method is executed by a computer in a semiconductor testing apparatus which comprises a read circuit, a determination circuit, and a faulty part specifying circuit, the program comprising:

instructions configured to read measurement data of an IDDQ measuring circuit configured to test semiconductor devices by applying an effective test vector, wherein the measurement data includes a test program, test vector data, data of good samples and faulty samples returned to a manufacturer;

instructions configured to supply the test vector data to good samples and faulty samples;

instructions configured to determine a range of pass/fail decision criteria and effective address pairs for testing semiconductor devices in a manufacturing process;